



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® 2in1 Wall & Ceiling Spray Texture: Popcorn Water Based

PRODUCT DESCRIPTION

DAP® 2in1 Wall & Ceiling Spray Texture Popcorn Water Based is an innovative technology system that allows you to tackle wall, ceiling & hard to reach areas with just one can. DAP's Aim Tech adjustable nozzle can be easily rotated upwards to spray at almost any angle achieving maximum coverage. Its ergonomic system provides professional hopper results and ultimate spray control. The aerosol can is extremely easy to use, offers a wide fan for even coverage without excessive dripping or clogging. Fast dry time of 30 minutes. Superior paintability; no priming needed and won't soften or drag. Interior/Exterior.

PACKAGING	COLOR	UPC
20 oz can	White	7079850025

KEY FEATURES & BENEFITS

- Ideal for vertical, overhead and hard to reach areas
- Wide coverage with even spray application
- Excellent match to textured surfaces
- 30 minute paint ready time depending on temperature, humidity & application thickness
- Strong and durable cure
- Low odor
- Easy water clean-up

SUGGESTED USES

USE FOR REPAIRING TEXTURED SURFACES:

- Drywall
- Stucco
- Plaster

FOR BEST RESULTS



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

- Shake well before spraying
- Apply in temperatures above 40°F
- Spray using intermittent bursts
- Dispense a quick burst on scrap material to activate product flow
- Practice applying on scrap material before use
- Store away from direct heat in temperatures ranging from 40°F to 90°F

APPLICATION

Surface Preparation

Surface must be clean, dry, structurally sound and free of all foreign material.

Make any necessary repairs to surface and ensure it is smooth and dry prior to applying spray texture.

Product Application

1. **UNLOCK** tab by bending backwards. THIS IS A RE-LOCKING TAB AND NOT MEANT TO BE BROKEN OFF.
2. **ADJUST** nozzle upward to desired spray angle, can rotate up to 60 degrees. BE SURE TO POINT AWAY FROM FACE AND PEOPLE.
3. **SHAKE** can upside down vigorously for more than one minute after hearing mixing marble moving freely in the can. **IMPORTANT** Dispense a quick burst of material on scrap material to activate before applying to surface.
4. **SPRAY** holding can approximately 12 to 18 inches away from surface using intermittent bursts, sweeping across the repair in a quick, continuous motion. For superior blending, feather texture into surrounding repair area. Add coverage as needed to match texture density, by applying in layers and waiting for each layer to dry before applying another layer. If not satisfied, scrape off and reapply. **IMPORTANT** be sure that the area is well ventilated and proper safety gear is worn.
5. **PAINT: PAINTING IS NOT REQUIRED FOR FINISHING.** If painting is needed, allow texture to dry for 30 minutes prior to painting. Dry time may be longer in cooler/humid conditions or with thicker applications. Follow paint manufacturer's instructions for best results. For exterior or wet application areas, protect with waterproof paint/coating.
6. **CLEAN-UP** tools and area with towel and warm water. Place nozzle in the upright position, invert can, pointing the top straight down. Spray onto a disposable surface until no texture sprays outs. Be sure to remove any texture build up from tip/nozzle to prevent material drying on tip/nozzle.
7. **STORE**, adjust spray nozzle angle to starting position and re-lock using tab. Store container in a cool, dry place away from extreme heat or cold.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Appearance/Consistency	White textured material
Base Polymer	Acrylic Latex
Weight % Solids	46
Density (lbs per gallon)	10.4



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Odor	Low odor
Clean Up	Water
Shelf Life	12 months
Coverage	12 sq. ft.
Typical Application Properties	
Application Temperature Range	Best between 65°F - 80°F
Typical Cured Performance Properties	
Service Temperature Range	Above 40° F

CLEAN UP & STORAGE

Clean up excess wet spray texture with warm water and soap. Excess dried spray texture must be cut or scraped away. Clean skin with warm water and soap. Store container in a cool, dry place away from extreme heat or cold.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

Limited Warranty: If product fails to perform as directed within one year from the date of purchase, call 1-888-DAP-TIPS with your sales receipt and product container available for replacement product or sales price refund. DAP will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com